

R115560

101950035

1 pcs



Both sides fitted with two ST PC connectors.
Fiber: MM G50/125 (OM2).
Cable: F8 3 x6 mm, orange.

010.1254.2 / similar product

TECHNICAL DATA

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Protection class IP	IP 20
Connector class	connector
Protection class IP (A)	IP 20
Number of connectors (A)	2
Protection class IP (B)	IP 20
Number of connectors (B)	2
Cable type	Patch cord, polarity A-B
Jacket material	LSZH
Cable jacket characteristics	Cable, metal-free Zero-halogen Flame-retardant
Cable overall diameter	3 x 6 mm (± 0.15)
Connector type (A)	ST
Polishing plug (A)	PC
Attenuation grade IL (A)	C
Return loss grade RL (A)	3
Connector color (A)	metallic
Connector type (B)	ST
Polishing plug (B)	PC
Attenuation grade IL (B)	C
Return loss grade RL (B)	3
Connector color (B)	metallic
Fiber type	multimode (MM)

R115560

101950035

1 pcs

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Fiberdiameter	G50/125µm
Patch cord type	duplex figure 8

MECHANICAL DATA

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	5.0 m / 16 ft
Color	orange